



Routing Protocols on Mantes-A Literature Survey

A.Radhika *
Senior Asst Prof,
CSE Dept,
S.R.K Institute of Technology,
Vijayawada-3,AP, India,
radhisunil@yahoo.com

Dr.D.Haritha
Professor & Head ,
CSE Dept,
S.R.K Institute of Technology,
Vijayawada-3,AP, India

Abstract: Mobile ad hoc networks (MANETs) are the networks without infrastructure support. Mobile ad hoc network have dynamic topology which is prone to malicious traffic analysis. These intermediate nodes are a threat to network security. A passive attacker can perform traffic analysis against interceptable routing formation embedded in routing messages and data packets. Adversaries, if allowed to trace network routes and information patterns of nodes, may affect covert operations. To overcome the issues related to passive attack, we need to propose a better routing scheme which hides the essential details but at the same time satisfies the requirements of a routing protocol.

Keywords: MANET, Proactive and Reactive, Hybrid routing protocols.

I. INTRODUCTION

Active research work for MANETs is carrying on mainly in the fields of Medium Access Control (MAC), routing, resource management, power control, and security. Because of the importance of routing protocols in dynamic multihop networks, lot of MANET routing protocols have been proposed in the last few years. Considering the special properties of MANET, when thinking about any routing protocol, generally the following properties are expected, though all of these might not be possible to incorporate in a single solution

- A routing protocol for MANET should be distributed in manner in order to increase its reliability.
- A routing protocol must be designed considering unidirectional links because wireless medium may cause a wireless link to be opened in unidirectional only due to physical factors.
- The routing protocol should be power-efficient.
- The routing protocol should consider its security.
- A hybrid routing protocol should be much more reactive than proactive to avoid overhead.
- A routing protocol should be aware of Quality of Service (QoS).

A. Classification of Routing Protocols for MANET

MANET routing protocols could be broadly classified into two major categories: Proactive and Reactive.

Proactive Routing Protocols: Proactive protocols continuously learn the topology of the network by exchanging topological information among the network nodes. Thus, when there is a need for a route to a destination, such route information is available immediately. If the network topology changes too frequently, the cost of maintaining the network might be very high. If the network activity is low, the information about actual topology might even not be used. **Reactive Routing Protocols:** The reactive routing protocols are based on some sort of query-reply dialog. Reactive protocols proceed for establishing route(s) to the destination only when the need arises. They do not need periodic transmission of topological information of the network.

a. Hybrid Routing Protocols: Often reactive or proactive feature of a particular routing protocol might not be enough; instead a mixture might yield better solution. Hence, in the recent days, several hybrid protocols are also

proposed. Based on the method of delivery of data packets from the source to destination, classification of MANET routing protocols could be done as follows:

b. Unicast Routing Protocols: The routing protocols that consider sending information packets to a single destination from a single source.

c. Multicast Routing Protocols: Multicast is the delivery of information to a group of destinations simultaneously, using the most efficient strategy to deliver the messages over each link of the network only once, creating copies only when the links to the destinations split. Multicast routing protocols for MANET use both multicast and unicast for data transmission.

Multicast routing protocols for MANET can be classified again into two categories: Tree-based multicast protocol and Mesh-based multicast protocol. Mesh-based routing protocols use several routes to reach a destination while the tree-based protocols maintain only one path.

II. PROPOSED PROACTIVE ROUTING PROTOCOLS: MAJOR FEATURES

A. Dynamic Destination-Sequenced Distance-Vector Routing Protocol (DSDV)

DSDV[1] is developed on the basis of Bellman-Ford routing[2] algorithm with some modifications. In this routing protocol, each mobile node in the network keeps a routing table. Each of the routing table contains the list of all available destinations and the number of hops to each. Each table entry is tagged with a sequence number, which is originated by the destination node. Periodic transmissions of updates of the routing tables help maintaining the topology information of the network. If there is any new significant change for the routing information, the updates are transmitted immediately. So, the routing information updates might either be periodic or event driven.

DSDV protocol requires each mobile node in the network to advertise its own routing table to its current neighbors. The advertisement is done either by broadcasting or by multicasting. By the advertisements, the neighboring nodes can know about any change that has occurred in the network due to the movements of nodes. The routing updates could be sent in two ways: one is called a “full dump” and another is “incremental.” In case of full dump, the entire routing table is sent to the neighbors, where as in case of incremental update, only the entries that require changes are sent.

B. Wireless Routing Protocol (WRP)

WRP[3] belongs to the general class of path-finding algorithms [2,4,5], defined as the set of distributed shortest path algorithms that calculate the paths using information regarding the length and second-to-last hop of the shortest path to each destination. WRP reduces the number of cases in which a temporary routing loop can occur. For the purpose of routing each node maintains four things: 1. A distance table 2. A routing table 3. A link-cost table 4. A message retransmission list (MRL). WRP uses periodic update message transmissions to the neighbors of a node. The nodes in the response list of update message (which is formed using MRL) should send acknowledgments. If there is no change from the last update, the nodes in the response list should send an idle Hello message to ensure connectivity. A node can decide whether to update its routing table after receiving an update message from a neighbor and always it looks for a better path using the new information. If a node gets a better path, it relays back that information to the original nodes so that they can update their tables. After receiving the acknowledgment, the original node updates its MRL. Thus, each time the consistency of the routing information is checked by each node in this protocol, which helps to eliminate routing loops and always tries to find out the best solution for routing in the network.

C. Cluster Gateway Switch Routing Protocol (CGSR)

CGSR [6] considers a clustered mobile wireless network instead of a “flat” network. For structuring the network into separate but interrelated groups, cluster heads are elected using a cluster head selection algorithm. By forming several clusters, this protocol achieves a distributed processing mechanism in the network. However, one drawback of this protocol is that, frequent change or selection of cluster heads might be resource hungry and it might affect the routing performance. CGSR uses DSDV protocol as the underlying routing scheme and, hence, it has the same overhead as DSDV. However, it modifies DSDV by using a hierarchical cluster-head-to-gateway routing approach to route traffic from source to destination. Gateway nodes are nodes that are within the communication ranges of two or more cluster heads. A packet sent by a node is first sent to its cluster head, and then the packet is sent from the cluster head to a gateway to another cluster head, and so on until the cluster head of the destination node is reached. The packet is then transmitted to the destination from its own cluster head.

D. Global State Routing (GSR)

In GSR protocol [7], nodes exchange vectors of link states among their neighbors during routing information exchange. Based on the link state vectors, nodes maintain a global knowledge of the network topology and optimize their

routing decisions locally. Functionally, this protocol is similar to DSDV, but it improves DSDV in the sense that it avoids flooding of routing messages.

E. Fisheye State Routing (FSR)

FSR [8] is built on top of GSR. The novelty of FSR is that it uses a special structure of the network called the “fisheye.” This protocol reduces the amount of traffic for transmitting the update messages. The basic idea is that each update message does not contain information about all nodes. Instead, it contains update information about the nearer nodes more frequently than that of the farther nodes. Hence, each node can have accurate and exact information about its own neighboring nodes.

F. Hierarchical State Routing (HSR)

HSR [9] combines dynamic, distributed multilevel hierarchical clustering technique with an efficient location management scheme. This protocol partitions the network into several clusters where each elected cluster head at the lower level in the hierarchy becomes member of the next higher level. The basic idea of HSR is that each cluster head summarizes its own cluster information and passes it to the neighboring cluster heads using gateways. After running the algorithm at any level, any node can flood the obtained information to its lower level nodes. The hierarchical structure used in this protocol is efficient enough to deliver data successfully to any part of the network.

G. Zone-Based Hierarchical Link State Routing Protocol (ZHLS)

In ZHLS protocol [10], the network is divided into nonoverlapping zones as in cellular networks. Each node knows the node connectivity within its own zone and the zone connectivity information of the entire network. The link state routing is performed by employing two levels: node level and global zone level. ZHLS does not have any cluster head in the network like other hierarchical routing protocols. Level topological information is distributed to all nodes. Since only zone ID and node ID of a destination are needed for routing, the route from a source to a destination is adaptable to changing topology. The zone ID of the destination is found by sending one location request to every zone.

H. Landmark Ad Hoc Routing (LANMAR)

LANMAR [10] combines the features of Fisheye State Routing (FSR) and Landmark Routing [11]. It uses the concept of landmark from Landmark Routing, which was originally developed for fixed wide area networks. A landmark is defined as a router whose neighbor routers within a certain number of hops contain routing entries for that router. Using this concept for the nodes in the MANET, LANMAR divides the network into several pre-defined logical subnets, each with a preselected landmark. All nodes in a subnet are assumed to move as a group, and they remain connected to each other via Fisheye State Routing (FSR). The routes to the landmarks, and hence the corresponding subnets, are proactively maintained by all nodes in the network through the exchange of distance vectors. LANMAR could be regarded as an extension of FSR, which exploits group mobility by summarizing the routes to the group members with a single route to a landmark.

I. Optimized Link State Routing (OLSR)

LSR [12] protocol inherits the stability of link state algorithm. This protocol performs hop-by-hop routing; that is each node in the network uses its most recent information to route a packet. Hence, even when a node is moving, its packets can be successfully delivered to it, if its speed is such that its movements could at least be followed in its neighborhood. The optimization in the routing is done mainly in two ways. Firstly, LSR reduces the size of the control packets for a particular node by declaring only a subset of links with the node's neighbors who are its multipoint relay selectors instead of all links in the network. Secondly, it minimizes flooding of the control traffic by using only the selected nodes, called multipoint relays to disseminate information in the network. As only multipoint relays of a node can retransmit its broadcast messages, this protocol significantly reduces the number of retransmissions in a flooding or broadcast procedure.

III. PROPOSED REACTIVE ROUTING PROTOCOLS MAJOR FEATURES

**I. **

A. Associativity Based routing (ABR)

ABR [13] protocol defines a new type of routing metric "degree of association stability" for mobile ad hoc networks. In this routing protocol, a route is selected based on the degree of association stability of mobile nodes. Each node periodically generates beacon to announce its existence. Upon receiving the beacon message, a neighbor node updates its own associativity table. For each beacon received, the associativity tick of the receiving node with the beaconing node is increased. A high value of associativity tick for any particular beaconing node means that the node is relatively static. Associativity tick is reset when any neighboring node moves out of the neighborhood of any other node. After the text edit has been completed, the paper is ready for the template. Duplicate the template file by using the Save As command, and use the naming convention prescribed by your conference for the name of your paper. In this newly created file, highlight all of the contents and import your prepared text file. You are now ready to style your paper; use the scroll down window on the left of the MS Word Formatting toolbar.

B. Signal Stability-Based Adaptive Routing Protocol (SSA)

SSA [14] protocol focuses on obtaining the most stable routes through an ad hoc network. The protocol performs on demand route discovery based on signal strength and location stability. Based on the signal strength, SSA detects weak and strong channels in the network. SSA can be divided into two cooperative protocols: the Dynamic Routing Protocol (DRP) and the Static Routing Protocol (SRP). DRP uses two tables: Signal Stability Table (SST) and Routing Table (RT). SST stores the signal strengths of the neighboring nodes obtained by periodic beacons from the link layer of each neighboring node. These signal strengths are recorded as weak or strong. DRP receives all the transmissions and, after processing, it passes those to the SRP. SRP passes the packet to the node's upper layer stack if it is the destination. Otherwise, it looks for the destination in routing table and forwards the packet. If there is no entry in the routing table for that destination, it initiates the route-finding process. Route-request packets are forwarded to the neighbors using the strong channels. The

destination, after getting the request, chooses the first arriving request packet and sends back the reply. The DRP reverses the selected route and sends a route-reply message back to the initiator of route request. The DRPs of the nodes along the path update their routing tables accordingly. In case of a link failure, the intermediate nodes send an error message to the source indicating which channel has failed. The source in turn sends an erase message to inform all nodes about the broken link and initiates a new route-search process to find a new path to the destination.

C. Temporarily Ordered Routing Algorithm (Tora)

TORA [15] is a reactive routing protocol with some proactive enhancements where a link between nodes is established creating a Directed Acyclic Graph (DAG) of the route from the source node to the destination. This protocol uses a "link reversal" model in route discovery. A route discovery query is broadcasted and propagated throughout the network until it reaches the destination or a node that has information about how to reach the destination. TORA defines a parameter, termed height. Height is a measure of the distance of the responding node's distance upto the required destination node. In the route discovery phase, this parameter is returned to the querying node. As the query response propagates back, each intermediate node updates its TORA table with the route and height to the destination node. The source node then uses the height to select the best route toward the destination. This protocol has an interesting property that it frequently chooses the most convenient route, rather than the shortest route. For all these attempts, TORA tries to minimize the routing management traffic overhead.

D. Cluster-Based Routing Protocol (CBRP)

CBRP [16] is an on-demand routing protocol, where the nodes are divided into clusters. When a node comes up in the network, it has the undecided state. The first task of this node is to start a timer and to broadcast a HELLO message. When a cluster-head receives this HELLO message, it replies immediately with a triggered HELLO message. After that, when the node receives this answer, it changes its state into the member state. But when the node gets no message from any cluster-head, it makes itself as a cluster-head, but only when it has bidirectional link to one or more neighbor nodes. Otherwise, when it has no link to any other node, it stays in the undecided state and repeats the procedure with sending a HELLO message again. Each node has a neighbor table. For each neighbor, the node keeps the status of the link and state of the neighbor in the neighbor table. A cluster head keeps information about all of its members in the same cluster. It also has a cluster adjacency table, which provides information about the neighboring clusters.

E. Dynamic Source Routing (DSR)

DSR [17] allows nodes in the MANET to dynamically discover a source route across multiple network hops to any destination. In this protocol, the mobile nodes are required to maintain route caches or the known routes. The route cache is updated when any new route is known for a particular entry in the route cache. Routing in DSR is done using two phases: route discovery and route maintenance. When a source node wants to send a packet to a destination, it first consults its route cache to determine whether it already knows about any route to the destination or not. If already there is an entry for

that destination, the source uses that to send the packet. If not, it initiates a route request broadcast. This request includes the destination address, source address, and a unique identification number. Each intermediate node checks whether it knows about the destination or not. If the intermediate node does not know about the destination, it again forwards the packet and eventually this reaches the destination. A node processes the route request packet only if it has not previously processed the packet and its address is not present in the route record of the packet. A route reply is generated by the destination or by any

of the intermediate nodes when it knows about how to reach the destination.

F. Ad Hoc On-Demand Distance Vector Routing (AODV)

AODV [18] is basically an improvement of DSDV. But AODV is a reactive routing protocol instead of proactive. It minimizes the number of broadcasts by creating routes based on demand, which is not the case for DSDV. When any source node wants to send a packet to a destination, it broadcasts a route request (RREQ) packet. The neighboring nodes in turn broadcast the packet to their neighbors and the process continues until the packet reaches the destination. During the process of forwarding the route request, intermediate nodes record the address of the neighbor from which the first copy of the broadcast packet is received. This record is stored in their route tables, which helps for establishing a reverse path. If additional copies of the same RREQ are later received, these packets are discarded. The reply is sent using the reverse path. For route maintenance, when a source node moves, it can reinitiate a route discovery process. If any intermediate node moves within a particular route, the neighbor of the drifted node can detect the link failure and sends a link failure notification to its upstream neighbor. This process continues until the failure notification reaches the source node. Based on the received information, the source might decide to re-initiate the route discovery phase.

IV. PROPOSED HYBRID ROUTING PROTOCOLS MAJOR FEATURES

A. Dual-Hybrid Adaptive Routing (DHAR)

DHAR is a particular proactive zone for that node. If for a given destination a node is not present within a particular proactive zone, reactive routing mechanism(query-reply) is used to establish the route to that node. Proactive routing mechanism is used within the proactive zone. Nodes within the proactive zone maintain routes proactively only with respect to the central node. In this protocol, proactive zones are created automatically if some destinations are frequently addressed or sought within the network. The proactive zones act as collectors of packets, which forward the packets efficiently to the destination, once the packets reach any node at the zone vicinity.

B. Neighbor-Aware Multicast Routing Protocol (NAMP)

NAMP [24] is a tree-based hybrid routing protocol, which utilizes neighborhood information. The routes in the network are built and maintained using the traditional request and reply messages or on-demand basis. This hybrid protocol uses neighbor information of two-hops away for transmitting

the packets to the receiver. If the receiver is not within this range, it searches the receiver using dominant pruning flooding method [25] and forms a multicast tree using the replies along the reverse path. Although the mesh structure is known to be more robust against topological changes, the tree structure is better in terms of packet transmission. As NAMP targets to achieve less end-to-end delay of packets, it uses the tree structure. There are mainly three operations addressed in NAMP: Multicast tree creation, Multicast tree maintenance and Joining and leaving of nodes from the multicast group. All the nodes in the network keep neighborhood information of up to two-hop away nodes. This neighborhood information is maintained using a proactive mechanism. Periodic hello packet is used for this. To create the multicast tree, the source node sends a flood request packet to the destination with data payload attached. This packet is flooded in the network using dominant pruning method, which actually minimizes the number of transmissions in the network for a particular flood request packet. During the forwarding process of the packet, each node selects a forwarder and creates a secondary forwarder list (SFL). The secondary forwarder list (SFL) contains the information about the nodes that were primarily considered as possible forwarders but finally were not selected for that purpose. Each intermediate node uses the chosen forwarder to forward the packet, but keeps the knowledge about other possible forwarders in SFL. Secondary forwarder list issued for repairing any broken route in the network. In fact, link failure recovery is one of the greatest advantages of NAMP.

V. OTHER ROUTING PROTOCOLS

In addition to the mentioned routing protocols for MANET, there are some other routing protocols that do not rely on any traditional routing mechanisms, instead rely on the location their IP addresses. But, in case of location-aware routing mechanisms, the nodes are often aware of their exact physical locations in the three-dimensional world. This capability might be introduced in the nodes using Global Positioning System (GPS) or with any other geometric methods. Based on these concepts, several geocast and location-aware routing protocols have already been proposed. The major feature of these routing protocols is that, when a node knows about the location of a particular destination, it can direct the packets toward that particular direction from its current position, without using any route discovery mechanism. Recently, some of the researchers proposed some location-aware protocols that are based on these sorts of idea. Some of the examples of them are Geographic Distance Routing (GEDIR)[26], Location-Aided Routing (LAR)[27], Greedy Perimeter Stateless Routing (GPSR)[28], Geo-GRID[29], Geographical Routing Algorithm (GRA)[30], etc. Other than these, there are a number of multicast routing protocols for MANET. Some of the mentionable multicast routing protocols are: Location-Based Multicast Protocol (LBM)[31], Multicast Core Extraction Distributed Ad hoc Routing (MCEDAR)[32], Ad hoc Multicast Routing protocol utilizing Increasing id-numbers (AMRIS)[33], Associativity-Based Ad hoc Multicast (ABAM)[34], Multicast Ad hoc On Demand Distance-Vector (MAODV) routing [35], Differentia Destination Multicast (DDM)[36], On-Demand Multicast Routing Protocol (ODMRP)[37], Adaptive Demand-driven Multicast Routing (ADMR) protocol [38], Ad hoc Multicast

Routing protocol (AMRoute) [39], Dynamic Core based Multicast routing Protocol (DCMP)[40], Preferred Link-Based Multicast protocol (PLBM)[41],etc. Some of these multicast protocols use location information and some are based on other routing protocols or developed just as the extension of another unicast routing protocol. For example, MAODV is the multicast-supporting Version of AODV.

VI. OTHER RECENT WORKS ON MANET ROUTING

This section mentions a list of references of the recent works on routing in MANET so that it could be used as a reference by the practitioners. Some of these works have taken the major routing protocols as their bases and some of them have enhanced various performances of the previous routing protocols. Mentionable recent works are: node-density-based routing [42], load-balanced routing [43], optimized priority based energy-efficient routing [44], reliable on-demand routing with mobility prediction [45], QoS routing [46], secure distributed anonymous routing protocol [47], robust position based routing [48], routing with group motion support [49], dense cluster gateway based routing protocol [50], dynamic backup routes routing protocol [51], gathering-based routing protocol [52], QoS-aware multicast routing protocol [53], recycled path routing [54], QoS multicast routing protocol for clustering in MANET [55], secure anonymous routing protocol with authenticated key exchange [56], self-healing on-demand geographic path routing protocol [57], stable weight-based on demand routing protocol [58], fisheye zone routing protocol [59], on-demand utility-based power control routing [60], secure position-based routing protocol [61], scalable multi-path on-demand routing [62], virtual coordinate-based routing [63], etc.

VII. CONCLUSION

This paper presents a number of routing protocols for MANET, which are broadly categorized as proactive and reactive. Proactive routing protocols tend to provide lower latency than that of the on-demand protocols, because they try to maintain routes to all the nodes in the network all the time. But the drawback for such protocols is the excessive routing overhead transmitted, which is periodic in nature without much consideration for the network mobility or load. On the other hand, though reactive protocols discover routes only when they are needed, they may still generate a huge amount of traffic when the network changes frequently. Depending on the amount of network traffic and number of flows, the routing protocols could be chosen. When there is congestion in the network due to heavy traffic, in general case, a reactive protocol is preferable. Sometimes the size of the network might be a major considerable point. For example, AODV, DSR, OLSR are some of the protocols suitable for relatively smaller networks, while the routing protocols like TORA, LANMAR,ZRP are suitable for larger networks. Network mobility is another factor that can degrade the performance of certain protocols. When the network is relatively static, proactive routing protocols can be used, as storing the topology information in such case is more efficient. On the other hand, as the mobility of nodes in the network increases, reactive protocols perform better. Overall, the answer to the debating point might be that the mobility and traffic pattern of the network must play the key role for

choosing an appropriate routing strategy for a particular network. It is quite natural that one particular solution cannot be applied for all sorts of situations and, even if applied, might not be optimal in all cases. Often it is more appropriate to apply a hybrid protocol rather than a strictly proactive or reactive protocol as hybrid protocols often possess the advantages of both types of protocols.

VIII. SCOPE FOR FUTURE RESEARCH

More and more efficient routing protocols for MANET might come in front in the coming future, which might take security and QoS (Quality of Service) as the major concerns. So far, the routing protocols mainly focused on the methods of routing, but in future a secured but QoS-aware routing protocol could be worked on. Ensuring both of these parameters at the same time might be difficult. A very secure routing protocol surely incurs more overhead for routing, which might degrade the QoS level. So an optimal trade-off between these two parameters could be searched. In the recent years some multicast routing protocols have been proposed. The reason for the growing importance of multicast is that this strategy could be used as a means to reduce bandwidth utilization for mass distribution of data. As there is a pressing need to conserve scarce bandwidth over wireless media, it is natural that multicast routing should receive some attention for ad hoc networks. So it is, in most of the cases, advantageous to use multicast rather than multiple unicast, especially in ad hoc environment where bandwidth comes at a premium. Ad hoc wireless networks find applications in civilian operations (collaborative and distributed computing) emergency search and-rescue, law enforcement, and warfare situations, where setting up and maintaining a communication infrastructure is very difficult. In all these applications, communication and coordination among a given set of nodes are necessary. Considering all these, in future the routing protocols might especially emphasize the support for multicasting in the network.

IX. REFERENCES

- [1] Perkins CE, Bhagwat P (1994) Highly Dynamic Destination-Sequenced Distance-Vector Routing (DSDV) for Mobile Computers. Proceedings of ACM SIGCOMM 1994:234–244
- [2] Cheng C, Riley R, Kumar SPR, Garcia-Luna-Aceves JJ (1989) A Loop-Free Extended Bellman-Ford Routing Protocol Without Bouncing Effect. ACM SIGCOMM Computer Communications Review, Volume 19, Issue 4:224–236
- [3] Murthy S, Garcia-Luna-Aceves JJ (1996) An Efficient Routing Protocol for Wireless Networks. Mobile Networks and Applications, Volume 1, Issue 2:183–197
- [4] Humblet PA (1991) Another Adaptive Distributed Shortest-Path Algorithm. IEEE Transactions on Communications, Volume 39, Issue 6:995–1003
- [5] Rajagopalan B, Faiman M (1991) A Responsive Distributed Shortest-Path Routing Algorithm Within Autonomous Systems. Journal of Internetworking Research and Experiment, Volume 2, Issue 1:51–69
- [6] Chiang C-C, Wu H-K, Liu W, Gerla M (1997) Routing in Clustered Multihop, Mobile Wireless Networks with Fading Channel. Proceedings of IEEE SICON:197–211

- [7] Chen T-W, Gerla M (1998) Global State Routing: A New Routing Scheme for Ad-hoc Wireless Networks. Proceedings of IEEE ICC 1998:171–175
- [8] Iwata A, Chiang C-C, Pei G, Gerla M, Chen T-W (1999) Scalable Routing Strategies for Ad Hoc Wireless Networks. IEEE Journal on Selected Areas in Communications, Volume 17, Issue 8:1369–1379
- [9] Jao-Ng M, Lu I-T (1999) A Peer-to-Peer Zone-Based Two-Level Link State Routing for Mobile Ad Hoc Networks. IEEE Journal on Selected Areas in Communications, Volume 17, Issue 8:1415–1425
- [10] Pei G, Gerla M, Hong X (2000) LANMAR: Landmark Routing for Large Scale Wireless Ad Hoc Network with Group Mobility. First Annual Workshop on Mobile and Ad Hoc Networking and Computing 2000 (MobiHoc 2000):11–18
- [11] Tsuchiya PF (1988) The Landmark Hierarchy: A New Hierarchy for Routing in Very Large Networks. Computer Communication Review, Volume 18, Issue 4:35–42
- [12] Jacquet P, Muhlethaler P, Clausen T, Laouiti A, Qayyum A, Viennot L (2001) Optimized Link State Routing Protocol for Ad Hoc Networks. IEEE INMIC 2001:62–68
- [13] Toh C-K (1996) A Novel Distributed Routing Protocol to Support Ad-Hoc Mobile Computing. Proceedings of the 1996 IEEE 15th Annual International Phoenix Conference on Computers and Communications:480–486
- [14] Dube R, Rais CD, Wang K-Y, Tripathi SK (1997) Signal Stability-Based Adaptive Routing (SSA) for Ad Hoc Mobile Networks. IEEE Personal Communications, Volume 4, Issue 1:36–45
- [15] Park VD, Corson MS (1997) A highly adaptive distributed routing algorithm for mobile wireless networks. Proceedings of IEEE INFOCOM 1997, Volume 3:1405–1413
- [16] Jiang M, Li J, Tay YC (1999) Cluster Based Routing Protocol (CBRP). IETF Draft, August 1999, available at <http://tools.ietf.org/html/draftietf-manet-cbrp-spec-01>. Accessed 21 February 2008
- [17] Broch J, Johnson DB, Maltz DA (1999) The Dynamic Source Routing Protocol for Mobile Ad Hoc Networks. IETF Draft, October, 1999, available at <http://tools.ietf.org/id/draft-ietf-manet-dsr-03.txt>. Accessed 21 February 2008
- [18] Perkins CE, Royer EM, Chakeres ID (2003) Ad hoc On-Demand Distance Vector (AODV) Routing. IETF Draft, October, 2003, available at <http://tools.ietf.org/html/draft-perkins-manet-aodvbis-00>. Accessed 21 February 2008
- [19] McDonald AB, Znati T (2000) A Dual-Hybrid Adaptive Routing Strategy for Wireless Ad-Hoc Networks. Proceedings of IEEE WCNC 2000, Volume 3:1125–1130
- [20] McDonald AB, Znati T (1999) A Mobility Based Framework for Adaptive Clustering in Wireless Ad-Hoc Networks. IEEE Journal on Selected Areas in Communications, Special Issue on Ad-Hoc Networks, Volume 17, Issue 8:1466–1487
- [21] Boppana RV, Konduru SP (2001) An Adaptive Distance Vector Routing Algorithm for Mobile, Ad Hoc Networks. Proceedings of IEEE INFOCOM 2001:1753–1762
- [22] Haas ZJ, Pearlman MR, Samar P (2002) The Zone Routing Protocol (ZRP) for Ad Hoc Networks. IETF draft, July 2002, available at <http://tools.ietf.org/id/draft-ietf-manetzone-zrp-04.txt>. Accessed 21 February 2008
- [23] Pathan A-SK, Alam MM, Monowar MM, Rabbi MF (2004) An Efficient Routing Protocol for Mobile Ad Hoc Networks with Neighbor Awareness and Multicasting. Proceedings of IEEE E-Tech, July, 2004:97–100
- [24] Lim H, Kim C (2000) Multicast Tree Construction and Flooding in Wireless Ad Hoc Networks. Proceedings of the 3rd ACM international Workshop on Modeling, Analysis and Simulation of Wireless and Mobile Systems:61–68
- [25] Lin X, Stojmenovic I (1999) GEDIR: Loop-Free Location Based Routing in Wireless Networks. Proceedings of the IASTED International conference on Parallel and Distributed Computing and Systems:1025–1028
- [26] Ko Y-B, Vaidya NH (2000) Location-Aided Routing (LAR) in Mobile Ad Hoc Networks. Wireless Networks, Volume 6:307–321
- [27] Karp B, Kung HT (2000) GPSR: Greedy Perimeter Stateless Routing for Wireless Networks. ACM MOBICOM 2000:243–254
- [28] Liao W-H, Tseng Y-C, Lo K-L, Sheu J-P (2000) GeoGRID: A Geocasting Protocol for Mobile Ad Hoc Networks based on GRID. Journal of Internet Technology, Volume 1, Issue 2:23–32
- [29] Jain R, Puri A, Sengupta R (2001) Geographical Routing Using Partial Information for Wireless Ad Hoc Networks. IEEE Personal Communications, Volume 8, Issue 1:48–57
- [30] Ko Y-B, Vaidya NH (1998) Location-based multicast in mobile ad hoc networks. Technical Report TR98-018, Texas A&M University.
- [31] Sinha P, Sivakumar R, Bharghavan V (1999) MCDAR: Multicast Core-Extraction Distributed Ad Hoc Routing. Proceedings of IEEE WCNC, Volume 3:1313–1317
- [32] Wu CW, Tay TC (1999) AMRIS: A Multicast Protocol for Ad Hoc Wireless Networks. IEEE MILCOM 1999, Volume 1:25–29
- [33] Toh C-K, Guichal G, Bunchua S (2000) ABAM: On-Demand Associativity-Based Multicast Routing for Ad Hoc Mobile Networks. Proceedings of IEEE VTS-Fall VTC 2000, Volume 3:987–993
- [34] Royer EM, Perkins CE (2000) Multicast Ad Hoc On-Demand Distance Vector (MAODV) Routing. IETF Draft, draft-ietf-manet-maodv-00, 15 July, 2000, available at <http://tools.ietf.org/html/draft-ietf-manet-maodv-00>. Accessed 21 February 2008
- [35] Ji L, Corson MS (2001) Differential Destination Multicast-A MANET Multicast Routing Protocol for Small Groups. Proceedings of IEEE INFOCOM 2001, Volume 2:1192–1201
- [36] Lee S, Su W, Gerla M (2002) On-Demand Multicast Routing Protocol in Multihop Wireless Mobile Networks. ACM/Kluwer Mobile Networks and Applications (MONET), volume 7, Issue 6:441–453
- [37] Jetcheva JG, Johnson DB (2001) Adaptive Demand-Driven Multicast Routing in Multi-Hop Wireless Ad Hoc Networks. Proceedings of ACM MobiHoc 2001:33–44

- [39] Xie J, Talpade RR, Mcauley A, Liu M (2002) AMRoute: Ad Hoc Multicast Routing Protocol. *Mobile Networks and Applications*, Volume 7, Issue 6:429–439
- [40] Das SK, Manoj BS, Murthy CSR (2002) A Dynamic Core Based Multicast Routing Protocol for Ad Hoc Wireless Networks. *Proceedings of ACM MobiHoc 2002*:24–35
- [41] Sisodia RS, Karthigeyan I, Manoj BS, Murthy CSR (2003) A Preferred Link Based Multicast Protocol for Wireless Mobile Ad Hoc Networks. *Proceedings of IEEE ICC 2003*, Volume 3:2213–2217
- [42] Quintero A, Pierre S, Macabeo B (2004) A routing protocol based on node density for ad hoc networks. *Ad Hoc Networks*, Volume 2, Issue 3:335–349
- [43] Saigal V, Nayak AK, Pradhan SK, MallR(2004) Load balanced routing in mobile ad hoc networks. *Computer Communications*, Volume 27, Issue 3:295–3054 Routing in Mobile Ad Hoc Networks 95
- [44] Wei X, Chen G, Wan Y, Mtenzi F (2004) Optimized priority based energy efficient routing algorithm for mobile ad hoc networks. *Ad Hoc Networks*, Volume 2, Issue 3:231–239 ISSN : 0975-3397 712
- [45] Wang N-C, Chang S-W (2005) A reliable on-demand routing protocol for mobile ad hoc networks with mobility prediction. *Computer Communications*, Volume 29, Issue 1:123–135
- [46] Buri K, Ersoy C (2005) Ad hoc quality of service multicast routing. *Computer communications*, Volume 29, Issue 1:136–148
- [47] Boukerche A, El-Khatib K, Xu L, Korba L (2005) An efficient secure distributed anonymous routing protocol for mobile and wireless ad hoc networks. *Computer Communications*, Volume 28, Issue 10:1193–1203
- [48] Moaveninejad K, Song W-Z, Li X-Y (2005) Robust position-based routing for wireless ad hoc networks. *Ad Hoc Networks*, Volume 3, Issue 5:546–559
- [49] Rango FD, Gerla M, Marano S (2006) A scalable routing scheme with group motion support in large and dense wireless ad hoc networks. *Computers&Electrical Engineering*, Volume 32, Issues 1–3:224–240
- [50] Ghosh RK, Garg V, Meitei MS, Raman S, Kumar A, Tewari N (2006) Dense cluster gateway based routing protocol for multi-hop mobile adhoc networks. *Ad Hoc Networks*, Volume 4, Issue 2:168–185
- [51] Wang Y-H, Chao C-F (2006) Dynamic backup routes routing protocol for mobile ad hoc networks. *Information Sciences*, Volume 176, Issue2:161–185
- [52] Ahn CW (2006) Gathering-based routing protocol in mobile ad hoc networks. *Computer Communications*, Volume 30, Issue 1:202–206
- [53] Sun B, Li L (2006) QoS-aware multicast routing protocol for Ad hoc networks. *Journal of Systems Engineering and Electronics*, Volume 17, Issue 2:417–422
- [54] Eisbrener J, Murphy G, Eade D, Pinnow CK, Begum K, Park S, Yoo SM, Youn J-H (2006) Recycled path routing in mobile ad hoc networks. *Computer Communications*, Volume 29, Issue 9:1552–1560
- [55] Layuan L, Chunlin L (2007) A QoS multicast routing protocol for clustering mobile ad hoc networks. *Computer Communications*, Volume 30, Issue 7:1641–1654
- [56] Lu R, Cao Z, Wang L, Sun C (2007) A secure anonymous routing protocol with authenticated key exchange for ad hoc networks. *Computer Standards & Interfaces*, Volume 29, Issue 5:521–527
- [57] Giruka VC, Singhal M (2007) A self-healing On-demand Geographic Path Routing Protocol for mobile ad-hoc networks. *Ad Hoc Networks*, Volume 5, Issue 7:1113–1128
- [58] Wang N-C, Huang Y-F, Chen J-C (2007) A stable weight-based on demand routing protocol for mobile ad hoc networks. *Information Sciences: an International Journal*, Volume 177, Issue 24:5522–5537
- [59] Yang C-C, Tseng L-P (2007) Fisheye zone routing protocol: A multilevel zone routing protocol for mobile ad hoc networks. *Computer Communications*, Volume 30, Issue 2:261–268
- [60] Min C-H, Kim S (2007) On-demand utility-based power control routing for energy-aware optimization in mobile ad hoc networks. *Journal of Network and Computer Applications*, Volume 30, Issue 2:706–727
- [61] Song J-H, Wong VWS, Leung VCM (2007) Secure position-based routing protocol for mobile ad hoc networks. *Ad Hoc Networks*, Volume 5, Issue 1:76–86
- [62] Reddy LR, Raghavan SV (2007) SMORT: Scalable multipath on demand routing for mobile ad hoc networks. *Ad Hoc Networks*, Volume 5, Issue 2:162–188
- [63] Zhao Y, Chen Y, Li B, Zhang Q (2007) Hop ID: A Virtual Coordinate- Based Routing for Sparse Mobile Ad Hoc Networks. *IEEE Transactions on Mobile Computing*, Volume 6, Issue 9:1075–1089

X. AUTHORS PROFILE

A.Radhika did M.C.A and M.Tech (Computer Science & Engineering) degree respectively. Presently pursuing Doctorate Degree (Ph.D) in Computer Science from Rayalaseema University, Kurnool and working as senior Assistant Professor in Computer Sciece & Engineering Department in S.R.K Institute of Technology. Her research interest includes Wireless networks, Mobile computing, Security, Routing Protocols, Trust metric measurement on MANET . Dr. D.Haritha received Ph.D in Computer Science in 2005 from Central University. She is working as Professor in the Department of Computer Science & Engineering. Her research interest includes computer networks and Image Processing. She is presently guiding 2 Ph.D scholars.